
 POLYFLOR VINYL FLOORING – Homogeneous Vinyl Flooring

POLYFLOR ULTRA XL PUR
POLYFLOR ULTRA XL PU
1. GENERAL INFORMATION

Well planned and regular maintenance, tailored to traffic conditions and frequencies, will help keep the floor covering in pristine condition. Without regular maintenance, standards of appearance, hygiene and cleanliness, as well as the life expectancy of the floor covering, will be compromised.

2. PREVENTATIVE MEASURES

In the initial stages of construction planning, attention should be paid to minimising the amount of dirt and water that can enter the building. To facilitate this we strongly recommend the installation of passive dirt barrier systems in all entrance areas e.g. scraper and moisture mats. The mats should be positioned to ensure that access cannot be gained without walking on them, ideally they should be at least six paces wide.

3. INITIAL CONSTRUCTION CLEAN

After the flooring has been installed, all dirt and construction debris should be completely removed and the floor swept clean.

For POLYFLOR ULTRA floor coverings use a stripper or an alkaline detergent. The slurry should be removed completely and the area rinsed thoroughly with clean water to restore a neutral pH value.

4. APPLICATION OF A FLOORDRESSING

After the floor covering has completely dried, it must be treated. Polymer dispersions or PU sealant systems have proven to be effective in this respect. The coats should be applied thinly and evenly. We recommend at least two applications and then polishing out.

Observe the corresponding manufacturer's instructions for the products used!

5. ROUTINE MAINTENANCE**Damp mop**

Damp mop the floor using a floor maintainer, then thoroughly wring out the mop and repeat to remove any residue.

Spray Cleaning / Burnishing

Burnish the floor by using a rotary machine (minimum 400 rpm) using a polishing brush and clean the floor by additionally using a spray cleaning product. This will add further protection and it will improve the appearance of the floor covering.

In both in cases use a soft pad (white, max. red.)

6. PERIODIC MAINTENANCE

If the floor has dirt build-up it may be necessary to clean the floor covering with an alkaline detergent according to the manufacturers' instructions.

7. REMOVAL OF A FLOORDRESSING

From time to time it will be necessary to strip back the polish layers, e.g. when routine maintenance does no longer bring about a satisfactory result. The interval is very much dependant on traffic conditions and maintenance methods. All soiling and any unsightly build up of polish should be removed by initially applying an emulsion polish stripper and the slurry should be removed completely. Then proceed as described in 4.

8. GENERAL INFORMATION

Always remove all chemical spillage immediately in order to avoid intensive damage of the original appearance.

Always follow the Health and Safety guidance issued by the cleaning product and machinery manufacturers. Always use the dilution rates and timings as recommended by the cleaning product manufacturers.

For further guidance contact objectflor Customer Technical Support or visit our homepage: www.objectflor.de