

SaarFloor Rubber Flooring

SaarFloor BERNSTEIN

SaarFloor DIAMANT

SaarFloor NOPPE

1. PREVENTATIVE MEASURES

A large part of the usual dirt can be avoided by dirt sluices in front of the entrances and clean running zones in the entrance areas and by including them in the maintenance cleaning. These zones should be at least six step lengths long and their entering should be obligatory.

2. INITIAL CONSTRUCTION CLEAN

48 hours after installation, proceed with the construction/intensive clean. All dirt and construction debris should be completely removed by using a suitable basic cleaner and a mono-pad rotary machine with a red pad (only smooth rubbers) or a scrubber. Remove the dirt liquor completely and neutralise the floor with clean water.

3. APPLICATION OF A FLOORDRESSING

Every initial construction cleaning or basic cleaning must be followed by an application of a floor dressing immediately, before the floor is walked on. With the application the surface is given a protective maintenance film which reduces the dirt adhesion and routine maintenance.

TXL Surface

The initial construction or basic cleaning removes the production release film.

Afterwards a floor covering with a mop care product (based on water-soluble polymers) or an emulsion (wax-based care) can be applied. This new care film can be polished up afterwards and in connection with regular maintenance cleaning.

On rubbers with a slightly structured surface (no pimple structure!) and in special cases on smooth coverings (e.g. with scratched surface) for facilitate routine maintenance and increasing the durability a care with polymer dispersions or a PU seal are possible – please observe the manufacturer's instructions.

Note: In this case the basic cleaning (points 2. and 5.) must be done with a green pad.

Apply two coats of an even thin film of undiluted polymer dispersions. Wait for drying and tread resistance before the second application. After the last drying, which should take place overnight, the flooring can be walked on.

4. ROUTINE MAINTENANCE

Daily cleaning

Mop, sweep or dry vacuum the floor, to remove dust and loose dirt. Treat stubborn dirt with a neutral detergent. Good cleaning results are guaranteed by 2-stage wiping (2 mop system with double bucket) with suitable wipe care or cleaning products.

Polishing / Cleaning

In this process, the flooring is polished with an appropriate machine and cleaned with the additional use of a spray cleaning product. Both causes a compression of the maintenance film and thus leads to an optical upgrading of the floor covering. In both cases a soft pad (white, max. red) must be used.

5. REMOVAL OF A FLOORDRESSING

A thorough clean may be necessary from time to time, if ongoing maintenance cleaning is no longer producing a satisfactory result. All dirt and care product residues are removed with a basic cleaner in combination with a single-disc machine and a red pad or a scrubbing brush completely removed. Then proceed as described under points 3. and 4.

General Information: Always follow the health and safety guidance issued by the cleaning product and machinery manufacturers. Always use the dilution rates and timings as recommended by the cleaning product manufacturers.

For further guidance contact objectflor Customer Technical Support or visit our homepage: www.objectflor.de