









POLYSAFE™ QUATTRO PUR

POLYSAFE QUATTRO PUR provides a safe footing in wet areas, even when soap residue increases the risk of slipping. The fine texture of the flooring ensures maximum protection in many sectors – with or without shoes.

Characteristics	Standards	Unit	POLYSAFE™ QUATTRO PUR
Type of floor covering	EN 13845		PVC covering with particle-based increased slip resistance
Surface treatment			PUR
Description			 non-directional, with chips
Colours			12
Special characteristics			 safety flooring perfect for wet/bare-foot areas
Total weight	EN ISO 23997	g/m ²	2700
Performance classification	EN ISO 10874		 23 34 43
Gauge	EN ISO 24346	mm	 2,0
Packaging roll size	EN ISO 24341	m / m ²	 2 m x 20 m / 40 m ²
Residual indentation	EN ISO 24343-1	mm	≤ 0,1
Colour fastness to artificial light	EN ISO 105-B02	level	≥ 6
Behaviour to fire	EN 13501-1		B _{fl} - s1
Slip resistance	EN 13845 DIN 51130 / DIN EN 16165 Ann B		ESb/ESf R11
Pendulum test – to check the flooring for slip			 50+
Impact sound reduction	EN ISO 10140-3	dB	2
Electrostatic properties when walked on	EN 1815	kV	≤ 2, antistatic
Chemical resistance	EN ISO 26987		*
Abrasion group	EN 13845		50.000 cycles
Castor chair suitability	ISO 4918		yes, type W, EN 12529
Underfloor heating suitability	EN 1264-2		suitable, max. 27 °C
VOC emissions	Floorscore Finnish M1 Classification AgBB VOC test		certified certified very low emissions
	EN 14041		










All POLYFLOR commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

* Resistant depending on concentration and time of exposure, in case of increased impact of oils, grease, acids, alkalis and other aggressive chemicals – please contact us.

Subject to change due to further technical development.