

POLYFLOR VINYL FLOORING – Safety Vinyl Flooring with PUR surface treatment

**POLYSAFE™
QUATTRO PUR**
**POLYSAFE™
STANDARD PUR**
**POLYSAFE™
VERONA PUR**
**POLYSAFE™
WOOD FX PUR**
1. GENERAL INFORMATION

Well planned and regular maintenance, tailored to traffic conditions and frequencies, will help keep the floor covering in pristine condition. Without regular maintenance, standards of appearance, hygiene and cleanliness, as well as the life expectancy of the floor covering, will be compromised.

2. PREVENTATIVE MEASURES

In the initial stages of construction planning, attention should be paid to minimising the amount of dirt and water that can enter the building. To facilitate this we strongly recommend the installation of passive dirt barrier systems in all entrance areas e.g. scraper and moisture mats. The mats should be positioned to ensure that access cannot be gained without walking on them, ideally they should be at least six paces wide.

3. INITIAL CONSTRUCTION CLEAN

After the flooring has been installed, all dirt and construction debris should be completely removed and the floor swept clean. For floor coverings with a PUR surface treatment a PU- or intensive cleaner has to be used and diluted following the manufacturer's instructions. The slurry should be removed completely and the area rinsed thoroughly with clean water to restore a neutral pH value.

4. APPLICATION OF A FLOORDRESSING

It is not necessary to apply such a protection to objectflor floor coverings with a PUR surface treatment.

5. ROUTINE MAINTENANCE**By hand:**

Good cleaning results are achieved by using a two-stage cleaning process (double mop system with a mobile double bucket unit) or with a special single-stage cleaning process using suitable care products.

By machine:

Cleaning by machine is suitable for large, clear areas. In this case, special machine cleaners are used in accordance with the cleaning product manufacturer's recommendations.

Spray Cleaning/Burnishing

Burnish the floor by using a rotary machine using a polishing brush and clean the floor by additionally using a spray cleaning product. This will add further protection and it will improve the appearance of the floor covering.

6. PERIODIC MAINTENANCE

If the floor has dirt build-up it may be necessary to clean the floor covering with an alkaline detergent according to the manufacturers' instructions.

7. REMOVAL OF A FLOORDRESSING

From time to time it will be necessary to strip back the polish layers, e.g. when routine maintenance does no longer bring about a satisfactory result. The interval is very much dependant on traffic conditions and maintenance methods. All soiling and any unsightly build up of polish should be removed by initially applying an emulsion polish stripper and the slurry should be removed completely.

8. GENERAL INFORMATION

Always remove all chemical spillage immediately in order to avoid intensive damage of the original appearance.

When choosing cleaning- and care products ensure that they complement each other and follow the manufacturer's instructions. The anti-slip properties of the security flooring must not be compromised.

For further guidance contact objectflor Customer Technical Support or visit our homepage: www.objectflor.de